

OVERHEAD STIRRER

BOECO OVERHEAD STIRRER OSD-20

- ▶ With digital display
- ▶ Robust, slimline, ergonomic design
- ▶ With constant power-drive
- ▶ Two speed ranges for universal use from 60-2.000 rpm
- ▶ Push-through agitator shafts (only when stationary)

Technical details

Stirring quantity (H ₂ O):	20 L.
Max.viscosity:	10.000 mPas
Motor rating input/output:	70 / 35 W
Output at stirring shaft:	26 W
Max. ON-time	100%
Max. torque at chuck (100rpm)	150 Ncm
Speed range I (50 Hz)	60 - 500 rpm.
Speed range II (50 Hz)	240 - 2.000 rpm
Speed display:	digital
Chuck range:	0,5 - 10 mm
Diameter:	13 mm
Length of extension arm:	160 mm
Protection class:	IP 20
(acc. to DIN EN 60529)	
Dimensions in mm (WxDxH):	88 x 212 x 294
Net weight:	approx 3,1 kg

The OSD-20 conforms to the CE mark and all relevant EC standards and DIN norms and has been manufactured under ISO 9001:2000

Code	Description
BOE 8901160	BOECO overhead stirrer OSD-20, 220-240V, 50/60 Hz, package , incl Plate stand R 1826, Boss head clamp R 182 and Propeller stirrer R 1342
BOE 8901161	BOECO overhead stirrer OSD-20, 115 V, 50/60 Hz, package , incl Plate stand R 1826, Boss head clamp R 182 and Propeller stirrer R 1342

ACCESSORIES INCLUDED:



BOECO OVERHEAD STIRRER OSD-20